

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

SECTION 1. IDENTIFICATION

Product name : ISOFLEX NBU 15

Article-No. : 004026

Manufacturer or supplier's details

Company name of supplier : Klüber Lubrication NA LP
9010 CR 2120
Tyler, Texas 75707
Phone: (903) 534-8021
Fax: (903) 581-4376

32 Industrial Drive
Londonderry, NH 03053
Phone: (603) 647-4104
Fax: (603) 647-4106

E-mail address of person responsible for the SDS : mcm@us.kluber.com
Material Compliance Management

Emergency telephone number : +1-517-545-7070 NCEC

Recommended use of the chemical and restrictions on use

Recommended use : Grease

Restrictions on use : Restricted to professional users.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Mineral oil.

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Synthetic hydrocarbon oil
ester oil
barium complex soap

Components

Chemical name	CAS-No.	Concentration (% w/w)
Barium compound	Proprietary	Trade secret (>= 30 - < 60)
White mineral oil (petroleum)	8042-47-5	Trade secret (>= 30 - < 60)
Polyalphaolefin	Proprietary	Trade secret (>= 10 - < 30)

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
Do not induce vomiting without medical advice.
- Most important symptoms and effects, both acute and delayed : No information available.
None known.
- Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Metal oxides

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Do not breathe vapours, aerosols. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product.

Conditions for safe storage : Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

ISOFLEX NBU 15

Version 1.1 Revision Date: 11/30/2021 Date of last issue: 05/20/2021 Date of first issue: 05/20/2021 Print Date: 02/22/2022

White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1 (2011-07-01)
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
		TWA (Mist)	5 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	NIOSH REL (2013-10-08)
		ST (Mist)	10 mg/m3	NIOSH REL (2013-10-08)

Engineering measures : none

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P

Hand protection

Material : Nitrile rubber

Break through time : > 10 min

Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : beige

Odour : characteristic

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available
Combustible Solids

Flammability (liquids) : Sustains combustion

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : < 0.001 hPa (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : 0.99 (68 °F / 20 °C)
Reference substance: Water
The value is calculated

Bulk density : Not applicable

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Viscosity
 Viscosity, dynamic : No data available
 Viscosity, kinematic : Not applicable
 Explosive properties : Not explosive
 Oxidizing properties : No data available
 Sublimation point : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.
 Chemical stability : Stable under normal conditions.
 Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
 Conditions to avoid : No conditions to be specially mentioned.
 Incompatible materials : No materials to be especially mentioned.
 Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.
 Acute inhalation toxicity : Remarks: This information is not available.
 Acute dermal toxicity : Remarks: This information is not available.

Components:

Barium compound:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: Directive 67/548/EEC, Annex V, B.1.
 GLP: yes
 Assessment: The substance or mixture has no acute oral toxicity

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Polyalphaolefin:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 423
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

ISOFLEX NBU 15

Version 1.1 Revision Date: 11/30/2021 Date of last issue: 05/20/2021 Print Date: 02/22/2022
Date of first issue: 05/20/2021

Components:

Barium compound:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Polyalphaolefin:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

Barium compound:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Polyalphaolefin:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Barium compound:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

White mineral oil (petroleum):

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Polyalphaolefin:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Barium compound:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative
GLP: yes

White mineral oil (petroleum):

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Genotoxicity in vitro : Test Type: Ames test
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Polyalphaolefin:

Genotoxicity in vitro : Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Polyalphaolefin:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Components:

White mineral oil (petroleum):

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

Polyalphaolefin:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
Did not show teratogenic effects in animal experiments.

STOT - single exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

Barium compound:

NOAEL : 150 mg/kg

White mineral oil (petroleum):

NOAEL : 1,800 mg/kg
Exposure time : 90 d

ISOFLEX NBU 15

Version 1.1	Revision Date: 11/30/2021	Date of last issue: 05/20/2021 Date of first issue: 05/20/2021	Print Date: 02/22/2022
----------------	------------------------------	---	---------------------------

Aspiration toxicity

Product:

This information is not available.

Components:

White mineral oil (petroleum):

No aspiration toxicity classification

Polyalphaolefin:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Barium compound:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209
GLP: yes

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 1,000 mg/l
Exposure time: 21 d

Polyalphaolefin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 1,000 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 125 mg/l
Exposure time: 21 d

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Barium compound:

Biodegradability : Primary biodegradation
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 16.8 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

White mineral oil (petroleum):

Biodegradability : Primary biodegradation
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Polyalphaolefin:

Biodegradability : Primary biodegradation
Inoculum: activated sludge
Result: Not readily biodegradable.
Method: OECD Test Guideline 301B

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Barium compound:

Partition coefficient: n-octanol/water : log Pow: 0.9 - 18

White mineral oil (petroleum):

Partition coefficient: n-octanol/water : Pow: > 6

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Polyalphaolefin:

Partition coefficient: n-octanol/water : log Pow: > 6.5 (68 °F / 20 °C)

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No information on ecology is available.

Components:

White mineral oil (petroleum):

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

Polyalphaolefin:

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Barium compound	Proprietary	>= 30 - < 50 %
barium bis(dinonylnaphthalenesulphonate)	25619-56-1	>= 0.1 - < 1 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

Pennsylvania Right To Know

Barium compound	Proprietary
White mineral oil (petroleum)	8042-47-5
Polyalphaolefin	Proprietary
bis(2-ethylhexyl) sebacate	122-62-3
barium bis(dinonylnaphthalenesulphonate)	25619-56-1

Maine Chemicals of High Concern

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

Vermont Chemicals of High Concern

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

Washington Chemicals of High Concern

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

New York City Hazardous Substances

Barium compound	Proprietary
barium bis(dinonylnaphthalenesulphonate)	25619-56-1
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5

California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum)	8042-47-5
-------------------------------	-----------

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

ISOFLEX NBU 15

Version	Revision Date:	Date of last issue: 05/20/2021	Print Date:
1.1	11/30/2021	Date of first issue: 05/20/2021	02/22/2022

Revision Date : 11/30/2021

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.